

WATER REPELLENT

KL-17

Product Specifications

KL-17 Water repellent for brick, masonry and concrete, brick, stucco and block surfaces is designed to prevent moisture penetration, migration and intrusion. KL-17 is a unique nonflammable, aqueous solution of sodium methyl silicate. It is supplied in a 15 percent solids solution in concentrated form. Silicates combined with moisture in the air and carbon dioxide in the atmosphere to form an insoluble, crystalline barrier in 24 hours. KL-17 creates a barrier within the surface that prevents water and moisture migration, yet allows the surface to breath. KL-17 can be painted over.

Suggested Applications

- **Brick, block, masonry walls and stucco surfaces**
- **Chimney caps**
- **Concrete slabs**
- **Poured and block foundations (interior and exterior), above and below grade**

- **Driveways, steps, patios and sidewalks**
- **Designed for use in areas where overlay applications are required**

Advantages

- **One-step, fast, easy, clean application**
- **Permits overlay applications such as paint, plaster, tile, vinyl flooring and carpet**
- **Nonflammable, odorless/colorless water-based solution**
- **Penetrates into the surface to form an insoluble barrier within 24 hours**
- **The seal actually becomes an integral part of the surface**
- **Dries within hours; slightly longer in humid conditions**
- **Prevents efflorescence**
- **Prevents surface deterioration**
- **Cleans with soap and water**



Rubber Polymer Corporation, Inc.
1030 Cambridge Square, Suite D
Alpharetta, Ga. 30004
770.410.1545 Fax: 770.410.1347
www.rpclink.com

1135 West Portage Trail Ext.
Akron, OH 44313
800.860.7721